EP 28908 (1)

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER

02245058

PUBLICATION DATE

28-09-90

APPLICATION DATE

17-03-89

APPLICATION NUMBER

01067322

APPLICANT: MITSUBISHI KASEI CORP;

INVENTOR: HAMASHIMA NORIYUKI;

 $-(C H_2)\cdot C O N H -$

INT.CL.

: C08L 77/00

TITLE

: POLYAMIDE FILM

ABSTRACT: PURPOSE: To prepare a polyamide film excellent in both the transparency and slip properties by forming a compsn., obtd. by adding a specific polyamide and a bismaleimide compd. to a polyamide mainly comprising capramide units into a film by a water-cooled inflation method.

> CONSTITUTION: A film is formed by a water-cooled inflation method from a resin compsn. obtd. by compounding 100 pts.wt. polyamide (A) having an m.p. higher than 215°C and mainly comprising capramide units with a polyamide (B) having the repeating units of the formula (wherein n is 9, 10, or 11) and a bismaleimide compd. If necessary, 0.01-0.5 pts.wt. inorg. filler may be added to the resin compsn. As said polyamide A, nylon 6 and nylon 6/66 are listed. Nylon 10 and nylon 11 are the examples of the polyamide B. Talc. kaolin, baked kaolin, and silica are pref. fillers because they are easily dispersed.

COPYRIGHT: (C)1990,JPO&Japio